

Xerox® PrimeLink®

C9265/C9275/C9281 Printer



Meet the Xerox® PrimeLink® C9265/C9275/C9281 Printer. Engineered to make a great first impression, these intuitive printers feature spot-on color fidelity, best-in-class media latitude, and professional finishing capabilities.

SYSTEM SPECIFICATIONS	XEROX® PRIMELINK® C9265 Printer		XEROX® PRIMELINK® C9275 Printer		XEROX® PRIMELINK® C9281 Printer	
SIMPLEX SPEEDS	COLOR	BLACK AND WHITE	COLOR	BLACK AND WHITE	COLOR	BLACK AND WHITE
8.5 x 11 in./A4 52 to 128 gsm* uncoated 129 to 176 gsm uncoated 177 to 220 gsm uncoated 221 to 300 gsm uncoated 301 to 350 gsm uncoated 106 to 176 gsm coated 177 to 220 gsm coated 221 to 256 gsm coated 257 to 300 gsm coated 301 to 350 gsm coated	Up to 65 ppm* Up to 43 ppm Up to 30 ppm Up to 30 ppm Up to 30 ppm Up to 65 ppm Up to 43 ppm Up to 30 ppm Up to 30 ppm Up to 30 ppm	Up to 65 ppm Up to 65 ppm Up to 51 ppm Up to 35 ppm Up to 35 ppm Up to 65 ppm Up to 43 ppm Up to 30 ppm Up to 30 ppm Up to 30 ppm	Up to 75 ppm Up to 51 ppm Up to 35 ppm Up to 35 ppm Up to 35 ppm Up to 51 ppm Up to 51 ppm Up to 35 ppm Up to 35 ppm Up to 30 ppm	Up to 75 ppm Up to 75 ppm Up to 51 ppm Up to 51 ppm Up to 35 ppm Up to 51 ppm Up to 51 ppm Up to 35 ppm Up to 35 ppm Up to 30 ppm	Up to 81 ppm Up to 51 ppm Up to 35 ppm Up to 35 ppm Up to 35 ppm Up to 51 ppm Up to 51 ppm Up to 35 ppm Up to 35 ppm Up to 35 ppm	Up to 81 ppm Up to 81 ppm Up to 51 ppm Up to 51 ppm Up to 35 ppm Up to 51 ppm Up to 51 ppm Up to 35 ppm Up to 35 ppm Up to 35 ppm
11 x 17 in./A3 52 to 105 gsm uncoated 106 to 128 gsm uncoated 129 to 176 gsm uncoated 177 to 220 gsm uncoated 221 to 300 gsm uncoated 301 to 350 gsm uncoated 106 to 176 gsm coated 177 to 220 gsm coated 221 to 350 gsm coated	Up to 34 ppm Up to 34 ppm Up to 21 ppm Up to 18 ppm Up to 18 ppm Up to 18 ppm Up to 21 ppm Up to 21 ppm Up to 21 ppm Up to 18 ppm	Up to 34 ppm Up to 34 ppm Up to 34 ppm Up to 27 ppm Up to 18 ppm Up to 18 ppm Up to 21 ppm Up to 21 ppm Up to 21 ppm Up to 18 ppm	Up to 37 ppm Up to 37 ppm Up to 27 ppm Up to 18 ppm Up to 18 ppm Up to 18 ppm Up to 27 ppm Up to 27 ppm Up to 27 ppm Up to 16 ppm	Up to 37 ppm Up to 37 ppm Up to 27 ppm Up to 27 ppm Up to 27 ppm Up to 18 ppm Up to 27 ppm Up to 27 ppm Up to 27 ppm Up to 16 ppm	Up to 42 ppm Up to 42 ppm Up to 27 ppm Up to 18 ppm Up to 18 ppm Up to 18 ppm Up to 27 ppm Up to 27 ppm Up to 27 ppm Up to 18 ppm	Up to 42 ppm Up to 42 ppm Up to 27 ppm Up to 18 ppm Up to 18 ppm Up to 18 ppm Up to 27 ppm Up to 27 ppm Up to 27 ppm Up to 18 ppm
12 x 18 in./SRA3 52 to 105 gsm uncoated 106 to 128 gsm uncoated 129 to 176 gsm uncoated 177 to 220 gsm uncoated 221 to 300 gsm uncoated 301 to 350 gsm uncoated 106 to 176 gsm coated 177 to 220 gsm coated 221 to 350 gsm coated	Up to 30 ppm Up to 30 ppm Up to 20 ppm Up to 16 ppm Up to 16 ppm Up to 16 ppm Up to 20 ppm Up to 20 ppm Up to 20 ppm Up to 16 ppm	Up to 30 ppm Up to 30 ppm Up to 30 ppm Up to 24 ppm Up to 16 ppm Up to 16 ppm Up to 20 ppm Up to 20 ppm Up to 20 ppm Up to 16 ppm	Up to 34 ppm Up to 34 ppm Up to 24 ppm Up to 16 ppm Up to 16 ppm Up to 16 ppm Up to 24 ppm Up to 24 ppm Up to 24 ppm Up to 16 ppm	Up to 34 ppm Up to 34 ppm Up to 34 ppm Up to 24 ppm Up to 16 ppm Up to 16 ppm Up to 24 ppm Up to 24 ppm Up to 24 ppm Up to 16 ppm	Up to 38 ppm Up to 38 ppm Up to 24 ppm Up to 16 ppm Up to 16 ppm Up to 16 ppm Up to 24 ppm Up to 24 ppm Up to 24 ppm Up to 16 ppm	Up to 38 ppm Up to 38 ppm Up to 38 ppm Up to 24 ppm Up to 16 ppm Up to 16 ppm Up to 24 ppm Up to 24 ppm Up to 24 ppm Up to 16 ppm

*Grams per square meter (gsm); Pages per minute (ppm).

Xerox® PrimeLink® C9265/C9275/C9281 Printer

Monthly Duty Cycle	Up to 500,000 pages (maximum volume capacity expected in any one month, not expected to be sustained regularly) ¹
Average Monthly Print Volume (AMPV)	Up to 75,000 pages per month ²
Technology	Ultra-Low-Melt High Definition Emulsion Aggregate (HD EA) Toner with advanced LED imaging technology and 2400 x 2400 dpi* resolution
Control Panel Languages	International English, International French, Italian, German, International Spanish, Arabic, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Turkish, Greek, Russian, Czech, Polish, and Romanian
ACCESSORIES (Note: Available accessories may vary by geography)	
Optional	Xerox® EX-i C9200 Series Print Server Powered by Fiery® (FS600 Platform) Xerox® EX C9200 Series Print Server Powered by Fiery® (FS600 Platform) Offset Catch Tray and Offset Catch Tray Fan Kit One-Tray Xerox® High Capacity Feeder One-Tray Xerox® Oversized High Capacity Feeder with storage cabinet Two-Tray Xerox® Oversized High Capacity Feeder Xerox® Interface Decurler Module Xerox® Business Ready Finisher 2.0 (requires a Vertical Transport Kit) Xerox® Business Ready Booklet Finisher 2.0 Xerox® Production Ready Finisher (requires Interface Decurler Module) Xerox® Production Ready Booklet Maker Finisher (requires Interface Decurler Module) Xerox® Production Ready Plus Finisher Plockmatic Pro450e/Pro435e Booklet Maker Xerox® Dual High Capacity Stacker Xerox® C/Z Folder GBC® AdvancedPunch Pro™ GBC® eWire GBC® AdvancedLam Pro™ Inline Laminator Xerox® Crease and Two-Sided Trimmer Xerox® SquareFold® Trimmer Module Xerox® Inserter Convenience Stapler Foreign Device Interface Kit PostScript Kit VoIP (Voice over Internet Protocol) Fax (Software (SW)) Kit Fax Kits Xerox® SIPRNet Enablement Kit Smart Card Enablement Kit Xerox® Integrated RFID Card Reader Optical Character Recognition (OCR) Kit USB Hub Kit WiFi Kit Xerox® FreeFlow® VI Compose Xerox® FreeFlow® VI Design Pro Banner Feed Guide Work Surface Top Tray Aligner Top Tray Extension Kit for Banners (requires Production Ready Finisher) Envelope Support Kit User Interface (UI) App Xerox® Job Progress Light

*Dots per inch (dpi)

ELECTRICAL REQUIREMENTS			
North America	Voltage: 110 to 127V Frequency: 50/60 Hz +/- 10V, 16 A		
Europe	Voltage: 220 to 240V Frequency: 50/60 Hz +/- 3 %, 10 A		
Accessories North America: Europe:	Each module requires 120V, 15 A Each module requires 220V, 10 A		
POWER CONSUMPTION			
Standby	195 W		
Running (Average)	PrimeLink® C9265: 1,224 Watts; PrimeLink® C9275: 1,774 Watts; PrimeLink® C9281: 2,104 Watts		
Sleep Mode (Average)	0.5 W (default time to Sleep Mode = 1 minute)		
Low Power Mode	150 W		
Sleep Mode (Recovery)	30 seconds		
OPERATING ENVIRONMENT			
Required Temperature Range	50° to 82° F/10° to 28° C (Relative Humidity less than 62.5 % when the temperature is 90° F/32° C or lower)		
Required Relative Humidity	15 % to 85 % (no condensation)		
Sound Pressure Levels	Running: 76 db(A) or lower Standby: 58 db(A) or lower		
Weight (Approximate Base Unit Only)	542 lbs./246 kg		
DIMENSIONS (Estimated Sizes for Individual Modules)	WIDTH	DEPTH	HEIGHT
Base Unit	30.7 in./780 mm	31.2 in./793 mm	45.4 in./1,154 mm
Base Unit with Offset Catch Tray and Bypass Open	62 in./1,575 mm	31.2 in./793 mm	45.4 in./1,154 mm
Business Ready Finisher 2.0	30.4 in./771 mm	27.2 in./692 mm	41.5 in./1,054 mm
Business Ready Booklet Finisher 2.0	30.6 in./776 mm	27.2 in./692 mm	41.5 in./1,054 mm
Business Ready Booklet Finisher 2.0 and C/Z Folder	39.9 in./1,013 mm	27.2 in./692 mm	41.5 in./1,054 mm
Production Ready Finisher and Interface Decurler Module	47 in./1,195 mm	28.5 in./725 mm	47.2 in./1,200 mm
Prodution Ready Booklet Maker Finisher and Interface Decurler Module	48.5 in./1,232 mm	28.5 in./725 mm	47.2 in./1,200 mm
Production Ready Booklet Maker Finisher and C/Z Folder	57.8 in./1,469 mm	28.5 in./725 mm	47.2 in./1,200 mm

Xerox® PrimeLink® C9265/C9275/C9281 Printer

Crease and Two-Sided Trimmer	23.8 in./605 mm	28.5 in./725 mm	39.1 in./992 mm
Interface Decurler Module	13.38 in./340 mm	28.5 in./725 mm	39.1 in./992 mm
SquareFold® Trimmer	42 in./1,066 mm	28.5 in./725 mm	21.7 in./552 mm
Insertor	6.5 in./165 mm	28.5 in./725 mm	48.6 in./1,235 mm
High Capacity Feeder	15.3 in./389 mm	24 in./610 mm	14.8 in./377 mm
One-Tray Oversized High Capacity Feeder	38.9 in./988 mm	30 in./762 mm	39 in./992 mm
Two-Tray Oversized High Capacity Feeder	38.9 in./988 mm	30 in./762 mm	39 in./992 mm

CERTIFICATIONS (To view the latest list of certifications, go to [xerox.com/OfficeCertifications](https://www.xerox.com/OfficeCertifications))

Graphic Arts Credentials	PANTONE® Matching System* PANTONE® GOE* PANTONE® PLUS* Adobe® PDF Print Engine* Adobe® PostScript® 3™** FOGRA Certification** IDEAlliance Digital Press Certified* to GRACoL® specifications** *Requires an additional Fiery® Print Server option **Coming in 2025
---------------------------------	---

PAPER HANDLING

SINGLE-PASS DUPLEX AUTOMATIC DOCUMENT FEEDER (DADF): NETWORK SCANNING

Capacity³	250 sheets of plain paper—20 lb./75 gsm
Speed	Up to 270 ipm color/270 ipm black-and-white (two-sided, 8.5 x 11 in./A4)
Weights	16 to 53 lb. bond/38 to 200 gsm

TRAY 5 (BYPASS)

Capacity³	250 sheets
Sizes	Custom sizes: 3.93 x 5.82 in. to 13 x 19.2 in./100 x 148 mm to 330 x 488 mm XLS sheet size: Up to 13 x 51 in./330 x 1,300 mm
Weights	16 lb. bond to 129 lb. cover/52 to 400; XLS sheet: 52-220 gsm; limit XLS in Tray 5 (Bypass) to 5 or fewer sheets
Envelope Capacity	30 to 50 envelopes
Envelope Sizes	#10 Commercial, Monarch (including custom size), C4, C5 (Available as Tray 5 (Bypass)). Paper Size Default within tools. Run flap open at the trail edge. Custom sizes: 7.5 x 6.7 in. to 9.45 x 6.81 in./190 x 170 mm to 240 x 173 mm. Digital or Laser Printer Grade recommended.
Envelope Weights	64 to 150 gsm

TRAYS 1 TO 4

Capacity³	Tray 1: 540 sheets Tray 2: 540 sheets Tray 3: 890 sheets Tray 4: 1,280 sheets
Total Capacity³	3,500 sheets (including Tray 5: 250 sheets)

Xerox® PrimeLink® C9265/C9275/C9281 Printer

Sizes	Tray 1: 5.5 x 8.5 in. to 12 x 18 in./A5 to SRA3 Tray 2: 5.5 x 8.5 in. to 11 x 17 in./A5 to A3 Tray 3: 7.25 x 10.5 in. to 8.5 x 11 in./B5, A4 Tray 4: 7.25 x 10.5 in. to 8.5 x 11 in./B5, A4
Weights	Trays 1 and 2: 16 lb. bond to 111 lb. cover/60 to 300 gsm (52 to 300 gsm uncoated; 106 to 300 gsm coated) Trays 3 and 4: 16 lb. bond to 111 lb. cover/60 to 300 gsm (52 to 300 gsm uncoated; 106 to 300 gsm coated)

(OPTIONAL) HIGH CAPACITY FEEDER (HCF)*

Capacity³	2,000 sheets
Sizes	7.25 x 10.5 in., 8.5 x 11 in./184.2 x 266.7 mm, 279.4 x 215.9 mm (B5, A4)
Weights	16 lb. bond to 80 lb. cover/60 to 220 gsm (uncoated and coated)

(OPTIONAL) OVERSIZED HIGH CAPACITY FEEDER (OHCF): ONE- OR TWO-TRAY OPTIONS

Capacity³	One-Tray OHCF: 2,000 sheets with Storage Cabinet Two-Tray OHCF: 4,000 sheets Tray 5 (Bypass): Up to 250 sheets; XLS capacity varies by media; limit XLS in Tray 5 (Bypass) to 5 or fewer sheets
Sizes	One-Tray OHCF: Tray 6: 3.9 x 5.8 in./100 x 148 mm to 13 x 19.2 in./330 x 488 mm Two-Tray OHCF: Trays 6 and 7: 3.9 x 5.8 in./100 x 148 mm to 13 x 19.2 in./330 x 488 mm Custom sizes via Tray 5 (Bypass): One-Tray OHCF: 13 x 26 in. (XLS/Banner) Two-Tray OHCF: 13 x 51 in. (XLS/Banner)
Weights	One-Tray OHCF: 52 to 350 gsm (52 to 350 gsm uncoated; 106 to 350 gsm coated) Two-Tray OHCF: 52 to 400 gsm (52 to 400 gsm uncoated; 106 to 400 gsm coated)

TOTAL CAPACITY

Standard Capacity	3,500 sheets (includes Tray 5 and Trays 1–4)
Maximum Capacity	7,500 sheets (includes Tray 5, Trays 1–4, and Two-Tray Oversized High Capacity Feeder)
Two-Sided	All Trays (1–4) up to 300 gsm auto duplex Trays 5–7 up to 350 gsm auto duplex Note: Extra-Long Sheets (XLS)/Banner media can only run simplex, up to 220 gsm

FINISHING

OFFSET CATCH TRAY

Capacity³	Up to 500 sheets stacking
-----------------------------	---------------------------

(OPTIONAL) BUSINESS READY FINISHER 2.0

Capacity³	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual-position or 4-position staple) 11 x 17 in., 8.5 x 14 in./A3 or 200 sets (single-position staple) 8.5 x 11 in./A4
Sizes	4 x 6 in. to 13 x 19.2 in./A5 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling 5.5 x 8.5 in./A5 output to Top Tray; punch and offset
Weights	16 lb. bond to 129 lb. cover/60 to 400 gsm (coated and uncoated) Top Tray 16 lb. bond to 94 lb. cover/60 to 256 gsm (coated and uncoated) Stacker Tray
Stapling	Single and multi-position stapling Auto stapling (50 sheets maximum)—24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, A4 Cover, Executive, 8 x 10 in., 8.5 x 13 in., 11 x 15 in., 215 x 315 mm, B4 and B5 sizes supported
Hole Punch North America: Europe:	2–3-Hole Punch 2–4-Hole Punch 4-Hole Swedish Punch (Optional)

(OPTIONAL) BUSINESS READY BOOKLET MAKER FINISHER 2.0	
Capacity³	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 unstapled. Stacking XLS output quantity is limited Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3/SRA3 unstapled or 200 stapled sets of 8.5 x 11 in./A4 (single-position, dual-position, or 4-position stapling) or 100 stapled sets of 11 x 17 in./A3/SRA3
Sizes	4 x 6 in. to 12 x 18 in./A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling 5.5 x 8.5 in./A5 output to Top Tray; punch and offset
Weights	Top Tray and Stacker Tray: 16 lb. bond to 129 lb. cover/52 to 400 gsm (coated and uncoated) Booklet Tray: 16 lb. bond to 110 lb. cover/52 to 256 gsm (coated and uncoated) Stacker
Stapling	Single and multi-position stapling Auto stapling (50 sheets maximum)—24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, A4 Cover, Executive, 8 x 10 in., 8.5 x 13 in., 11 x 15 in., 215 x 315 mm, B4, and B5 sizes supported
Hole Punch North America: Europe:	2–3-Hole Punch 2–4-Hole Punch 4-Hole Swedish Punch (Optional)
Booklet Maker	Saddle-stitch 2 to 20 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated), Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, B4, B5, Executive, 8.5 x 13 in., 11 x 15 in., 215 x 315 mm, 12 x 18 in., 13 x 19.2 in., and SRA3 supported
(OPTIONAL) C/Z FOLDER UNIT FOR BUSINESS READY FINISHER 2.0	
Types	C-Fold, Z-Fold, and Z-Half-Fold
Capacity³	40 sheets
Sizes	C-Fold and Z-Fold: Letter—8.5 x 11 in./A4 Short Edge First (SEF) only Z-Half-Fold: Tabloid—11 x 17 in./A3 only
Weights	16 to 24 lb. bond/60 to 90 gsm
Output Tray	Envelope Tray: C-Fold, Z-Fold, and Tri-Fold Stacker Tray or Top Tray: Z Half-Fold
(OPTIONAL) PRODUCTION READY FINISHER: REQUIRES INTERFACE DECURLER MODULE	
Capacity	Top Tray: 500 sheets of 20 lb. bond/80 gsm, 8.5 x 11 in./A4 Stacker Tray: 3,000 sheets of 20 lb. bond/80 gsm, 8.5 x 11 in./A4
Sizes	4 x 6 in. to 13 x 26 in./A6 to SRA3
Weights	16 lb. bond to 129 lb. cover/60 to 400 gsm (coated and uncoated) Top Tray 16 lb. bond to 94 lb. cover/60 to 256 gsm (coated and uncoated) Stacker Tray
Multi-position Stapling	Up to 100 sheets of 20 lb. bond/80 gsm
Hole Punch North America: Europe:	2–3-Hole Punch 2–4-Hole Punch 4-Hole Swedish Punch (Optional)
Inserters Capacity: Sizes: Weights:	200 sheets of 126 gsm 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 11 x 17 in./A3, A4, B4, B5 18 lb. bond to 130 lb. cover/64 to 350 gsm
Decurling	Active decurling included in the base unit; optional decurling included with the Interface Decurler Module and Standard Finisher, featuring Bi-Directional decurling with both Auto and Manual settings

(OPTIONAL) PRODUCTION READY FINISHER WITH BOOKLET MAKER: REQUIRES INTERFACE DECURLER MODULE	
Capacity	Top Tray: 500 sheets of 20 lb. bond/80 gsm, 8.5 x 11 in./A4 Stacker Tray: 2,000 sheets of 20 lb. bond/80 gsm, 8.5 x 11 in./A4
Sizes	4 x 6 in. to 13 x 19.2 in./A6 to SRA3
Weights	18 lb. bond to 129 lb. cover/60 to 400 gsm (coated and uncoated) Top Tray 18 lb. bond to 94 lb. cover/60 to 256 gsm (coated and uncoated) Stacker Tray 18 lb. bond to 94 lb. cover/60 to 256 gsm (coated and uncoated) Booklet Maker
Multi-Position Stapling	Up to 100 sheets of 20 lb. bond/80 gsm
Hole Punch North America: Europe:	2–3-Hole Punch (Optional) 2–4-Hole Punch (Optional) 4-Hole Swedish Punch (Optional)
Inserter Capacity: Sizes: Weights:	200 sheets of 128 gsm 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 11 x 17 in./A3, A4, B4, B5 18 lb. bond to 80 lb. cover/64 to 220 gsm
Decurling	Included with Interface Module and Standard Finisher, featuring Bi-Directional decurling with both Auto and Manual settings
Booklet Making Capacity	Saddle-stitch 2 to 30 sheets of 90 gsm (uncoated) or up to 15 sheets of 120 gsm (coated); Bi-Fold up to 5 sheets 8.5 x 11 in., 8.5 x 13 in., 8.5 x 14 in., 9 x 11 in., 11 x 15 in., 11 x 17 in., 12 x 18 in./A4, B4, A3, SRA3
(OPTIONAL) PRODUCTION READY FINISHER PLUS: REQUIRES INTERFACE DECURLER MODULE	
Provides the same function as the Production Ready Finisher with a 500-sheet Top Tray and a 2,000-sheet Stacker Tray. Used to connect third-party inline finishing options. Includes Partner Finishing Interface Module (PFIM).	
(OPTIONAL) CREASE AND TWO-SIDED TRIMMER	
Sizes	Crease: 7.25 x 10.5 in. to 13 x 19.2 in./A4 to SRA3, custom sizes 7.2 x 8.3 in. to 13 x 19.2 in./ 182 x 210 mm to 330 x 488 mm Trim: 8 x 10 in. to 13 x 19.2 in./A4 to SRA3, custom sizes 7.2 x 10 in. to 13 x 19 in./ 182 x 257 mm to 330 x 488 mm
Weights	Crease: 18 lb. bond to 129 lb. cover/60 to 350 gsm Trim: 18 lb. bond to 129 lb. cover/60 to 350 gsm
(OPTIONAL) GBC® ADVANCEDPUNCH PRO™	
Punch Configuration Sizes	A3, A4, A5, SRA3, 8.5 x 11 in., 8.5 x 14 in., 11 x 17 in., and 12 x 18 in.
Weights	20 lb. bond to 129 lb. cover/75 to 350 gsm (uncoated); 28 lb. bond to 129 lb. cover/106 to 350 gsm (coated)
Binding Dies	Wide selection of slide-in/slide-out GBC® punch die sets available
Note: When printing XLS with the GBC® AdvancedPunch Pro™, the Xerox® Inserter must be included in the system configuration	
(OPTIONAL) SQUAREFOLD® TRIMMER MODULE	
Capacity	Up to 30 sheets of 90 gsm
Sizes	Custom sizes: 8.5 x 11 in. to 12 x 18 in./A4 to SRA3
Weights	18 lb. bond to 94 lb. cover/64 to 220 gsm
(OPTIONAL) CONVENIENCE STAPLER	
Capacity	50 sheets (24 lb./90 gsm media)

Xerox® PrimeLink® C9265/C9275/C9281 Printer

Extra-Long Sheets (XLS) Finishing Limitations

XLS will output to Offset Catch Tray (OCT), Business Ready Top Tray, and Production Ready Top Tray. However, stacking quality will be limited.. The XLS Extension Tray Kit is available for the Production Ready Finisher to improve the stacking of multiple sheets.

When printing XLS with the GBC® AdvancedPunch Pro™, the Xerox® Inserter must be included in the system configuration.

PRINT

Print Resolution	Up to 2400 x 2400 dpi
Line Screens	600, 300, 200, and 150 Clustered Dot, 200 Rotated Line Screen (depending on the print server/controller selected)
Registration	- Advanced registration technology for tighter control - Simple Image Quality Adjustment (SIQA) for de-skewing, registration, and density uniformity (Available on all configurations as a Maintenance Tool; Alignment Adjustment) - Up to 0.5 mm; variation may occur based on paper size, tray, and environmental conditions
First-print-out-time	All models: 8-10 seconds
Print Drivers	Job Identification, Bi-Directional Status, Job Monitoring, Xerox® Global Print Driver®, Application Defaults, Xerox® Pull Print Driver, Universal Print For information about supported print drivers, please visit our Drivers and Downloads page and select your device

PRINT SOLUTIONS

Mobile Printing	Apple® AirPrint®, Mopria® Print, Mopria® Print Service Plug-in for Android, Xerox® @PrintByXerox App, Xerox® Workplace Suite Mobile Printing Solution, and Xerox® Workplace Cloud Mobile Printing Solution Learn more at xerox.com/MobileSolutions
------------------------	--

COPY

First-copy-out-time From the Platen: From the DADF:	As fast as/warmed-up state: C9265: Color 5.4/BW 4.1 C9275: Color 5.4/BW 4.1 C9281: Color 5.4/BW 4.1 As fast as/warmed-up state: C9265: Color 9.1/BW 6.9 C9275: Color 7.4/BW 5.9 C9281: Color 7.3/BW 5.8
Warm-up Time	90 seconds (from cold powered-down state to ready to copy)
Digital Imaging	Auto color Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, and map) Lighter/Darker Background suppression Auto and manual contrast Sharpness Color balance, color shift, and saturation
Reduce/Enlarge	Variable zoom from 25 % to 400 % in 1 % increments Anamorphic zoom Six user-programmable percentages
Special Features	Copy Features: Auto color Auto paper select Reduce and enlarge 25–400 % Pages per side Lighter/Darker Finishing: Lamination Staple Hole punch

	Folding Copy output (Collate/Uncollate) Output destination Face up/face down Original types: Photo and text, photo, text, and map Mixed Orientation Sharpness Saturation Image enhancement Color effects Color balance Color shift Gloss level Book copying: Two-sided book copying Edge erase Image shift Mirror image Negative image Image rotation Booklet creation Covers Posters Repeat image Preset repeat image Annotation Watermark Joint job Other: Auto tray switching Interrupt Automatic job recovery
SCAN	
Concurrency	Scan while printing or while it is transferring, scan to network, or fax jobs
Scan Features	Mixed-size originals Edge erase Reduction/Enlargement Fit to size Scan build job Compression quality/File size control Original type (photo and text, photo and text) Auto background and shadow suppression Job flow sheets Scan to USB Preview scan job
INPUT SPEED	
Resolution	Up to 270 images per minute (ipm) Duplex 600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi
Maximum Scan Area	Originals up to 11 x 17 in./A3
File Formats	PDF image only Searchable PDF (optional) PDF (A-1) TIFF V6

Scan Features	Mixed-size originals Edge erase Reduce/Enlarge Fit to size Quality file size Original type Background Scan to USB Scan to folder Preview scan job Shadow suppression Book scanning File naming PDF security Skew correction
Supported Scan Destinations	Scan to Email, Scan to Folder, Scan to PC, Scan to Mailbox (private and public), Scan to USB, FTP (File Transfer Protocol), and Scan to SMB (Server Message Block)
Scan to Email Features	Color scanning, auto color, grayscale, black and white Direct document email from the device Manual or directory Exchange/Notes/LDAP (Lightweight Directory Access Protocol) address searching Signing and encryption Email over SSL (Secure Sockets Layer) Preview scan job
Authentication	SMTP (Simple Mail Transfer Protocol) authentication, POP (Post Office Protocol) before SMTP, system credentials, and single sign-on (LDAP, SMB, and Kerberos authentication) Scanning security–TLS (Transport Layer Security)
FAX (OPTIONAL): ONE LINE FAX OPTIONS	
Maximum Scan Area	11 x 17 in./SEF
Fax Features	VoIP iFax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination
DEVICE MANAGEMENT	
XEROX® EMBEDDED WEB SERVER: INTEGRATED WEB PAGES PROVIDED BY THE DEVICE	
Remote UI	Providing remote view and operation of the PrimeLink® Printer Remote operations provide helpful collaborations, and training administrators can enable/disable both features and user restrictions
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts
Job Submission	Print ready files: PDF, XPS®, PCL® 6, HP-GL2 (direct submission), TIFF, JPEG and Adobe® PostScript® 3™ (highly recommended option) Output feature selection (two-sided, output color, collate, orientation, staple, hole punch, folding, and output destination) Delivery options (Immediate, sample set, delay and secure, save job, or reprint)
Device Administration	Allows simple, remote installation, setting of configuration options, and management of the device

Xerox® PrimeLink® C9265/C9275/C9281 Printer

Browsers	Internet Explorer Safari Mozilla Firefox Opera Chrome
Support	Install print/scan drivers, and online support is available via the web page
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, and Polish

REMOTE SERVICES

Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage; eliminates the need for time-consuming, end-user involvement, and ensures that meter reads are submitted to us on time
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® Devices based on actual usage, eliminating the need to manage supplies inventory manually

SECURITY

Features	Access controls AES 256-bit encryption Audit log Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification Domain filtering FIPS 140-3 Firmware verification Immediate disk overwrite IP address filtering IPsec Network authentication Pre-installed self-signed certificates Role-based permissions Secure print Security certificate management Smart card enablement (CAC/PIV/.NET) SNMPv3 TLS/SSL (TLS 1.0, 1.1, 1.2) SIPRnet TAA (Trade Agreements Act)/GSA (General Services Administration)
-----------------	--

PRINT SERVER

INTEGRATED COLOR SERVER FOR THE XEROX® PRIMELINK® C9200 SERIES PRINTER (REQUIRED)

Processor	1.6 GHz dual-core
Memory	4 GB RAM
System Disk	320 GB Hard Disk Drive
Display	10 in. color touchscreen flat-panel display
Device Operating System	Linux®
Page Description Languages (PDLs)	PDF, XPS®, PCL® 6, HP-GL2 (direct submission), TIFF, JPEG, and Adobe® PostScript® 3™ (highly recommended option)
Print Drivers Supported	Please refer to xerox.com/support for specifics. As new operating system versions are added, support is also added for the Xerox® PrimeLink® C9200 Series Printer. Also, note that there is more than one print driver based on the configuration purchased (e.g., digital front ends and Xerox® Global Print Driver®)
Print Features	Automatic two-sided Secure print

Xerox® PrimeLink® C9265/C9275/C9281 Printer

	Delay print Sample set Booklet creation Cover selection Paper selection by attribute N-up Watermarks Banner sheets Output tray selection Standard USB Paper catalog (up to 400 entries) Print Around/Tray Mismatch
Connectivity	Ethernet interface (10 MBTX/sec, 100 MBTX/sec, 1000 MBTX/sec)
ADDITIONAL PRINT SERVER OPTIONS	
XEROX® EX-i C9200 SERIES PRINT SERVER POWERED BY FIERY® (FS600 PLATFORM)	
Processor	Intel® G7400E Processor
Memory	8 GB
Hard Drive	500 GB HDD
Server Operating System	Linux®
File Formats	Adobe® PostScript® Level 1, 2, 3; Adobe® PDF; PDF/X-1a, 3, 4; Enhanced PCL® 6/PCL 5; Microsoft® Native Formats (doc/x, xls/x, pub/x, ppt/x) via the Fiery® driver or Fiery® Hot Folders; EPS and TIFF
Features	• Productivity starts with a fast RIP; the Integrated Fiery® Color Server enables you to print large and/or complex Microsoft® Office documents, PowerPoint® files, and color-critical PDFs accurately and quickly • Simplify and streamline your workflow; automate job submission of repetitive job types to achieve productive, error-free workflows with Hot Folders and Virtual Printers • Take advantage of commonly used Fiery® presets to save time when submitting jobs; with Fiery® server technology, even novice users can perform complex jobs using the preset drivers configured for the task • Get the color right; produce precise, exact color from all applications, platforms, and formats with Fiery® color management tools, including Fiery® TrueBrand and Fiery® Spot-On™ • Offer personalized printing with Fiery® FreeForm™ Create; quickly personalize existing files by adding various elements such as text, images, or barcodes • The Fiery® Essential Driver increases productivity with a simple, intuitive way to print standard office documents in just a few clicks; or, use the Xerox® Global Print Driver® • Easily print files with mixed paper sizes and types • Command WorkStation • Standard Fiery® JDF connectivity boosts digital workflow efficiency by integrating with existing prepress, web-to-print, or MIS/ERP systems to eliminate manual touchpoints, errors, and resource waste • Secure erase • Paper catalog • Fiery® Compose • Fiery® Remote Scan
Connectivity	Single and Dual TCP/IP connectivity for integration with Xerox Extensible Interface Platform® (EIP): • TCP/IP, Bonjour support, SNMP, Port 9100, IPP 2.0, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPv6 support, LDAP authentication • Native support for Universal Print by Microsoft® • Compliant with Mopria® industry standard
Additional Options	Packages/Suites/Kits: • Fiery® Color Profiler Suite with ES-3000 • Fiery® Automation Package • Fiery® ColorRight Package • Fiery® JobExpert and PDF Processing Kit

Xerox® PrimeLink® C9265/C9275/C9281 Printer

	Features (optional—available separately): • Fiery® Impose • Fiery® JobMaster
	For more information, go to xerox.com
XEROX® EX C9200 SERIES PRINT SERVER POWERED BY FIERY® (FS600 PLATFORM)	
Processor	Intel® Core™ i3-12100 Processor
Memory	8 GB
Hard Drive	1 TB HDD
Server Operating System	Microsoft® Windows 10 IoT Enterprise 2021 LTSC
Print Languages (PDL)	Adobe® PostScript® Level 3, Adobe® PDF, EPS, PCL® 6C, PCL 5, TIFF, JPG, Microsoft® native formats via Fiery® Hot Folders and Adobe® PDF Print Engine (APPE)
Features	• Job-based calibration integration – Fiery® Spot-On finds the best match of PANTONE®, PANTONE® Series, RGB, CMYK, L*a*b*, and Spot Colors—color modes for professional proofing and enhanced production color requirements—maximum print density • Easily handle heavy workloads and provide faster turnaround times with the most powerful DFE for the Xerox® PrimeLink® C9200 Series Printer; Fiery® Edge technology gets the most precise and stunning results from PrimeLink® printers; it achieves the best possible gamut for both spot and process color reproduction • The Fiery® Command WorkStation increases your production and reduces errors and waste by centralizing job management via its intuitive user interface; simplify your labor-intensive document composition and imposition tasks even more by using Fiery® Impose and Compose's intuitive interface • Print high-quality photos and images • Fiery® FreeForm™ Create for quick personalization; provides variable text, images, and barcode elements; supporting VDP formats like PDF/VT-1 and 2, PPML (Personalized Print Markup Language), VPS, and Xerox® VIPP® Language • Easily print files with mixed paper sizes and types • Paper catalog • Fiery® JDF • Fiery® JobExpert analyzes files and dynamically chooses the optimal print settings • Fiery® TrueBrand ensures accurate spot colors for all job types, even Microsoft® Office documents • FOGRA Certified
Connectivity	Single and Dual TCP/IP connectivity for Integration with Xerox Extensible Interface Platform® (EIP): • TCP/IP, Bonjour support, Simple Network Management Protocol (SNMP), Port 9100, IPP 2.0, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPv6 support, and LDAP authentication • Log in with single sign-on (SSO), native support for Universal Print by Microsoft® • Compliant with Mopria® industry standard
Additional Options	Packages/Suites/Kits: • Fiery® Color Profiler Suite With ES-3000 • Fiery® Graphic Arts Pro Package • Hard Drive Security Kit • Additional Drives Kit • Fiery® NX Station GL Features (optional—available separately): • Fiery® JobMaster
	For more information, go to xerox.com

Xerox® PrimeLink® C9265/C9275/C9281 Printer

SUPPLIES		YIELD	PART NUMBER
Toner Cartridges (Metered)	Black	34,500 pages ⁴	006R04847
	Cyan	37,500 pages ⁴	006R04848
	Magenta	37,500 pages ⁴	006R04849
	Yellow	37,500 pages ⁴	006R04850
Toner Cartridges (Sold)	Black	34,500 pages ⁴	006R04851 (North America, Western Europe) 006R04855 (All other regions)
	Cyan	37,500 pages ⁴	006R04852 (North America, Western Europe) 006R04856 (All other regions)
	Magenta	37,500 pages ⁴	006R04853 (North America, Western Europe) 006R04857 (All other regions)
	Yellow	37,500 pages ⁴	006R04854 (North America, Western Europe) 006R04858 (All other regions)
Our Customer Replaceable Component (CRU) (Drum Cartridge)	1 Common Cartridge for CMY and K	122,500 pages ⁴	013R00703
Waste Toner Container	1 Container	50,000 pages ⁴	008R08159

¹ Maximum volume capacity expected in any one month. Not expected to be sustained regularly.

² Expected regular monthly throughput.

³ Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

⁴ Approximate pages. Declared Yield based on 5-page job size, 30% color, and 70% black-and-white ratio, using letter/A4 media. Yield will vary based on media size, image coverage area, job run length, media orientation, and usage patterns. These yields are based on 5% coverage area.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program.

For more information, visit xerox.com/About-Xerox/Recycling.

Learn more at xerox.com/PrimeLink.

